GJI-S-12-0690 Electronic Supplement

S. Warden¹, S. Garambois², L. Jouniaux¹, D. Brito³, P. Sailhac¹ & C. Bordes³

¹Institut de Physique du Globe de Strasbourg, CNRS UMR 7516, Université de Strasbourg, Strasbourg, France ²ISTerre, Université Joseph Fourier, CNRS UMR 5275, Grenoble, France ³Laboratoire des fluides complexes et leurs réservoirs, Université de Pau et des Pays de l'Adour, CNRS UMR 5150, Pau, France

8 April 2013

1 GJI-S-12-0690 ELECTRONIC SUPPLEMENT

1.1 Comparison between laboratory dielectric constant measurements on sandstones at various frequencies

Figure 1 compiles the dielectric constant values measured on Berea sandstone samples of porosity ϕ =19.7 % at different saturation levels by Knight (1984) at frequencies of 57 kHz, 11.7 MHz and 13 MHz. The values measured by Gomaa (2008) at 100Hz for clean (clay-free) Aswan hematitic sandstone samples with 23 % porosity are also plotted. Finally, Figure 1 displays the dielectric constant as a function of saturation S_w as predicted by the CRIM formula for a clean sandstone with 23 % porosity.

1.2 Reciprocity test

Checking for the reciprocity of the Green's tensor is a common way to search for errors in a numerical program. In this Section, we show that the program we have developed under partial saturation conditions verifies these reciprocity relations for coupled seismic / electromagnetic waves. We consider a simple tabular model, consisting of a partially saturated sandstone layer with S_w =0.4, 30 m thick, on top of a saturated sandstone halfsace. We model two source-receiver configurations: 2 S. Warden, S. Garambois, L. Jouniaux, D. Brito, P. Sailhac & C. Bordes

• shallow source ($z_s=1$ m) and receivers set at depth ($z_r=59$ m), noted "down" in Figures 2 (a) and (c)), as most of the energy travels downwards.

buried source (z_s=59 m) with a string of shallow receivers (z_r=1 m), noted "up" in Figures 2
(b) and (d)).

In both configurations, a 10 m offset along y was introduced between the source and receivers. In Figure 2, we have modeled only the interfacial conversions. The notation "uz/Dx" (Figure 2 (a)) refers to the vertical displacement created by a dipole oriented along x. This seismogram correlates well with the electrogram displying the electric field along x obtained using a mehcanical source along z. The maximum amplitude for the "uz/Dx" case (5.049×10^{-6}) is close to the maximum amplitude obtained for the "Ex/Fz" case (5.016×10^{-6}) . In a similar way, the recordings displayed in Figures 2 (b) and (d) correlate well and show the same maxium amplitude (1.595×10^{-6}) .



Figure 1. Dielectric constant versus water saturation S_w as measured by Knight (1984) on Berea (ϕ =19.7 %) sandstone samples and Gomaa (2008) for Aswan (ϕ =23 %) sandstone. The results obtained with the CRIM formula for a sandstone with a porosity ϕ =23 % are also plotted for comparison.



Figure 2. Results of the reciprocity test described in Subsection 1.2.

4 S. Warden, S. Garambois, L. Jouniaux, D. Brito, P. Sailhac & C. Bordes

REFERENCES

Gomaa, M. M. N. R. C., 2008. Relation between electric properties and water saturation for hematitic sandstone with frequency, Published.

Knight, R. J., 1984. The dielectric constant of sandstones, 5 Hz to 13 MHz.